GNO GINEICO



5295 Plutone TRP

The Plutone spotlight range contains some of our most advanced LED technology. The Plutone TRP is a small yet powerful fitting featuring a 3 watt LED module. The Nichia™ LED chip produces a very high quality LED output with an average colour rendering index of 95. The spotlight is waterproof from both the front and rear and is available in various lens angles and colour temperatures. The TRG model features an innovative FS SYSTEM fixing method which allows the product to be installed from the front of the panel and not the rear like many spotlights of this kind. A simple key can be used to remove the product from the front for easy maintenance.

- Interior & exterior spotlight with flange-less design
- Excellent anti-glare properties with recessed LED source
- Galvanised brass face, black painted
- Custom finishes available on request
- Tempered glass lens
- Anodised aluminium heatsink
- Multiple lens angles available
- FS SYSTEM fixing method no need to prefit to ceiling panels
- Available in numerous white colour temperatures as well as red
- Weight (kg) 0.09
- Wattage 3W
- Input Voltage 10-30Vdc
- Bezel Size (mm) Ø36.00
- Cut-out Size (mm) Ø36.00
- Depth (mm) 50.00
- Finish Black



G45, 76-84 WATERWAY DRIVE COOMERA, QUEENSLAND, 4209, AUSTRALIA PHONE: (+61) 7 5556 0244 EMAIL: SALES@GINEICOMARINE.COM.AU WWW.GINEICOMARINE.COM.AU



Heat Dissipation

Heat dissipation is key to the performance and longevity of LED lighting. Our Power LED modules have been carefully designed to ensure that the heat is taken away from the LED chips and dissipated through the incorporated heat sink designed into the product housing.

Circuit board temperatures are closely monitored during the development phase of each product and appropriate heat dissipation can then be accurately calculated to ensure that product will continue to perform for many years.

Simple Frame-less Installation

The separate FS SYSTEM aluminium backing plate makes installation easy and swift. The backing plate can be screwed to the back side of the installation panel, allowing the frame-less fitting to click into place from the front. No need to pre-wire panels or fit lights in advance. Maintenance is also quick and easy, a special key allows the fitting to be removed from the front without the need to remove ceiling panels.

Not All Cones Are Equal

A choice of lens angles is available for this product which means that the perfect output can be selected for any given project. Selecting either standard, medium or narrow lenses can have a large effect on the overall lighting effect.

