



## ACTION

**Ceiling LED lamp with rectangular frame. White plastic frame. Compartment light. Installation on ceiling or wall.**

- Power type Constant Voltage
- Light source 0 x LED
- Supply 9 ÷ 16 V, 18 ÷ 32 V
- Power consumption 5 W, 10 W
- Current consumption 0.32 A @ 16V
- Average lifetime 50,000 h
- IP security degree 66
- Frame RECT. 5 1/2" x 4 9/16"
- Recess 1/2" (Thickness)
- Weight 150 gr
- Frame material PLASTIC
- Finishings WHITE 9010
- Light colours DAYLIGHT / DAYLIGHT-RED
- Mounting SCREWS
- Chromed frame available upon request



## 5W DAYLIGHT 3800-4100 °K

- CRI ≥ 80
- Angle 100°
- Light flow 314 lm
- Lighthness - distance 1 m/Ø 2.08 m/132.4 lux
- Lighthness - distance 2 m/Ø 4.16 m/33.1 lux
- Lighthness - distance 3 m/Ø 6.25 m/14.7 lux

## 10W DAYLIGHT 3800-4100 °K

- CRI ≥ 80
- Angle 100°
- Light flow 630 lm
- Lighthness - distance 1 m/Ø 2.26 m/266.1 lux
- Lighthness - distance 2 m/Ø 4.51 m/66.5 lux
- Lighthness - distance 3 m/Ø 6.77 m/29.6 lux

## 5W DAYLIGHT-RED

- CRI ≥ 80
- Angle 100°
- Light flow 314 lm
- Lighthness - distance 1 m/Ø 2.08 m/132.4 lux
- Lighthness - distance 2 m/Ø 4.16 m/33.1 lux
- Lighthness - distance 3 m/Ø 6.25 m/14.7 lux

## 10W DAYLIGHT-RED

- CRI ≥ 80
- Angle 100°
- Light flow 630 lm
- Lighthness - distance 1 m/Ø 2.26 m/266.1 lux
- Lighthness - distance 2 m/Ø 4.51 m/66.5 lux
- Lighthness - distance 3 m/Ø 6.77 m/29.6 lux

