



JO

Modern LED downlight made in 316 AISI stainless steel.

With IP65 rating, it is protected against humidity and water splashes, if installed properly. Effective lighting and optimal chromatic yield.

- Power type Constant Voltage
- Light source LED
- Supply 10 ÷ 30 V
- Power consumption 1,5W, 3W
- Current consumption 0.06 A @ 24V, 0.13A @ 24V
- Average lifetime 50,000 h
- Dimmable Yes
- IP security degree 65
- Frame Ø 1 21/32"
- Recess 3/4"
- Hole Ø 63/64"
- Frame material AISI 316 S/STEEL
- Finishes MIRROR POLISHED, SATIN, WHITE
- Light colours DAYLIGHT / WARM WHITE
- Mounting SCREWS



1,5W DAYLIGHT 3800-4100 °K

- CRI \geq 80
- Angle 15°
- Light flow 115 lm
- Lighthness - distance 1 m/ \varnothing 0.27 m/988.0 lux
- Lighthness - distance 2 m/ \varnothing 0.53 m/236.0 lux
- Lighthness - distance 3 m/ \varnothing 0.80 m/104.9 lux

1,5W WARM WHITE 2900-3100 °K

- CRI \geq 80
- Angle 15°
- Light flow 105 lm
- Lighthness - distance 1 m/ \varnothing 0.27 m/890.0 lux
- Lighthness - distance 2 m/ \varnothing 0.53 m/222.5 lux
- Lighthness - distance 3 m/ \varnothing 0.80 m/98.9 lux

3W DAYLIGHT 3800-4100 °K

- CRI \geq 80
- Angle 15°
- Light flow 138 lm
- Lighthness - distance 1 m/ \varnothing 0.18 m/746.8 lux
- Lighthness - distance 2 m/ \varnothing 0.37 m/186.7 lux
- Lighthness - distance 3 m/ \varnothing 0.55 m/83.0 lux

3W WARM WHITE 2900-3100 °K

- CRI \geq 90
- Angle 15°
- Light flow 104 lm
- Lighthness - distance 1 m/ \varnothing 0.18 m/560.1 lux
- Lighthness - distance 2 m/ \varnothing 0.37 m/140.0 lux

